U.S. Department of Transportation

800 Independence Ave., S.W Washington, D.C. 20591

Federal Aviation Administration

**Transmittal Letter 15-08** 

February 27, 2015

## PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

| AIRAC<br>DATE | STATE | CITY                         | AIRPORT                                       | FDC<br>NUMBER | FDC<br>DATE | SUBJECT                      |
|---------------|-------|------------------------------|---|---------------|-------------|------------------------------|
| 2-Apr-15      | GA    | Fort Stewart<br>(Hinesville) | Wright AAF (Fort<br>Stewart)/Midcoast<br>Rgnl | 5/1962        | 02/12/15    | RNAV (GPS) RWY 6L,<br>Orig-B |

FDC **5/1962** LHW IAP WRIGHT AAF (FORT STEWART)/MIDCOAST RGNL, FORT STEWART(HINESVILLE), GA. RNAV (GPS) RWY 6L, ORIG-B... LNAV VISIBILITY CATS C/D 1 5/8. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SAVANNAH/HILTON HEAD INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, LNAV CAT C AND D VISIBILITY 1/4 MILE, AND CIRCLING CAT C VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SAVANNAH/HILTON HEAD INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, LNAV CAT C AND D VISIBILITY 1/8 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE.

THIS IS RNAV (GPS) RWY 6L ORIG-C. 1502102103-PERM